Rotary Enclosed Isolators





Insulated 3 and 4 pole, CE marked, A/C isolators, suitable for disconnecting power supply to outdoor air conditioning condensing units.

Features

- Weatherproof to IP65
- Easy installation
- M20/25 knockouts up to 63A
- Handle lockable in off position
- Interlocked cover removable in off position only
- Earth and neutral terminals included
- Captive, retained cover screws
- Conforms to IEC 60947-3

Related Products

All Guards
All Brackets

The Package

• Rotary Enclosed Isolator •

Part Code	No. of Poles	Amps AC21	AC23 A 240VA	AC23 A 400VA	Cable Capacity		Height	Width	Depth
					Solid	Stranded			
IS-3P-20A	3	20 Amp	5.5 kW	3.7 kW	1-16mm²	0.75-10mm ²	175mm	114mm	135mm
IS-3P-32A	3	32 Amp	11 kW	7.5 kW	1-16mm²	0.75-10mm ²	175mm	114mm	135mm
IS-3P-40A	3	40 Amp	15 kW	11 kW	1-16mm²	0.75-10mm ²	175mm	114mm	135mm
IS-3P-63A	3	63 Amp	22 kW	18.5 kW	1-16mm²	0.75-10mm ²	175mm	114mm	135mm
IS-4P-20A-S	4	20 Amp	5.5 kW	3.7 kW	1-16mm²	0.75-10mm ²	125mm	100mm	120mm
IS-4P-20A	4	20 Amp	5.5 kW	3.7 kW	1-16mm²	0.75-10mm ²	175mm	114mm	135mm
IS-4P-32A-S	4	32 Amp	11 kW	7.5 kW	1-16mm²	0.75-10mm ²	125mm	100mm	120mm
IS-4P-32A	4	32 Amp	11 kW	7.5 kW	1-16mm²	0.75-10mm ²	175mm	114mm	135mm
IS-4P-40A	4	40 Amp	15 kW	11 kW	1-16mm²	0.75-10mm ²	175mm	114mm	135mm
IS-4P-63A	4	63 Amp	22 kW	18.5 kW	1-16mm²	0.75-10mm ²	175mm	114mm	135mm



