

NEW

Refrigeration & Air Conditioning Technology

SUPER EGO

A part of the ROTHENBERGER GROUP

Refrigerant Recovery Unit

Suitable for use with A1, A2L & A2 refrigerants recovers all commonly used CFC, HCF and HFC refrigerants including R32 and 1234yf



KEY FEATURES

Refrigerant Recovery Unit

- Compact, portable machine for all kinds of refrigerant recovery including R32 and 1234yf
- Light weight and weighs only 13 Kg
- 3 functions in 1
- High recovery rate 111 Kg liquid per Hr. (15 Kg per hr vapour)
- Input voltage 230V
- Purge function
- High Pressure safety shut off

Compressor: Oil less, air cooled 1 piston
Motor: 3/4 H.P
Motor speed: 1450rpm - 50Hz ,1760 - 60Hz
Current: 4A 220v, 8A 110v
Dimensions: 400 x 250 x 355mm
Power supply: 220-240v - 50-60Hz
Weight: 13Kg
Operating temperature: 0°C-40°C
High pressure safety shut-off 38.5bar/3850kPa(558psi)

Description	Pump Rating	Kg	No.
Rec R32	3/4hp 14550rpm	13kg	2664

Tel: 01273 455530
Email: sales@srw.co.uk
www.srw.co.uk

SUPER-EGO