

COMPRESSOR DEFINITION

Designation	NE K6187Z
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	268AG71

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	9.99	[cm ³] (0.610 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	18.120	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11	[kg] (24.25 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	9660A-XX-183	
3 Start capacitor	189-227(165)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0389/G9	
6 Start winding resistance	6.10	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.96	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	37.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	4.60	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3830	965	1122	486	5.82	24.83	7.88	1.99	2.31

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ASHRAE46 Fan				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1883	474	552	281	4.60	10.18	6.70	1.69	1.96
-10	(+14)	2361	595	692	306	4.70	12.81	7.72	1.95	2.26
-5	(+23)	2953	744	865	333	4.84	16.09	8.86	2.23	2.60
0	(+32)	3661	922	1073	363	5.02	20.03	10.08	2.54	2.95
+5	(+41)	4483	1130	1314	395	5.23	24.66	11.35	2.86	3.33
+10	(+50)	5420	1366	1588	429	5.49	30.01	12.64	3.19	3.70

TEST CONDITIONS: @115V60Hz		ASHRAE46 Fan				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1641	414	481	296	4.68	9.59	5.54	1.40	1.62
-10	(+14)	2062	520	604	328	4.85	12.09	6.29	1.58	1.84
-5	(+23)	2594	654	760	361	5.03	15.27	7.18	1.81	2.10
0	(+32)	3238	816	949	396	5.25	19.15	8.18	2.06	2.40
+5	(+41)	3993	1006	1170	431	5.49	23.77	9.27	2.34	2.72
+10	(+50)	4861	1225	1424	467	5.75	29.13	10.39	2.62	3.05

TEST CONDITIONS: @115V60Hz		ASHRAE46 Fan				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1444	364	423	303	4.73	9.19	4.77	1.20	1.40
-10	(+14)	1795	452	526	344	4.94	11.48	5.22	1.32	1.53
-5	(+23)	2254	568	660	385	5.18	14.48	5.85	1.47	1.71
0	(+32)	2821	711	827	426	5.43	18.23	6.61	1.67	1.94
+5	(+41)	3497	881	1025	468	5.69	22.74	7.48	1.88	2.19
+10	(+50)	4282	1079	1255	509	5.98	28.03	8.42	2.12	2.47

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.03 +0.07/+0.00	[mm]	(0.316" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		