



Vacuum Pumps SEGO VAC

SEGO VAC 6.0

DUAL VOLTAGE 2-STAGE VACUUM PUMP 6.0 CFM

KEY FEATURES

- Dual voltage 110V/230V
- · Solenoid non-return valve
- Vacuum gauge in Hg/mbar reading
- Detachable kettle type mains lead

Technical Details

Voltage: 110v-230v~ / 50-60hz

Free air displacement: 6.0 CFM

Ultimate vacuum: 15 micron

Number of stages: 2

Motor: 3/4HP

Intake Ports: 1/4" flare

Oil: 580ml

Dimensions: 395 x 145 x 297mm

T. NE

Description:	Pump Rating		Kg	No.
Sego Vac 6.0	6 CFM	170 l/min	16.5	1501R



Supplied with 5/16" & 3/8" Adaptors

Refrigerant Recovery Unit

SEGO RECV NOT FOR USE WITH HYDROCARBONS

Recovers all commonly used CFC, HCF and HFC refrigerants including R410A

KEY FEATURES

- · Lightweight and compact, weighs only 13kg
- High recovery rate, 111kg liquid per Hr. (15kg per Hr vapour)
- Dual voltage 110V/230V
- Purge function

Technical Details

Compressor: Oil less, air cooled 1 piston

Motor: 3/4 Hi

Motor speed: 1450rpm - 50hz, 1760 - 60hz

 Current:
 4A 220v, 8A 110v

 Dimensions:
 400 x 250 x 355mm

 Power supply:
 110/220-240v - 50-60hz



gerants	Kg	No.
HCFC, HFC	13	1400R
	<u> </u>	

Refrigerant Scale

SEGO SCL

DIGITAL ELECTRONIC REFRIGERANT SCALE 100Kg

KEY FEATURES

- · Hard wired hand held remote control with LCD
- Audible Alarm Battery operated
- Supplied in sturdy carrying case

Technical Details

Capacity: 100kg
Resolution: 5g
Accuracy: 0.05%



Description:	Capacity	No.
SEGO SCL	100kg	1401R

